

43 Sparta Avenue Newton, NJ 07860

Sales: (973) 300-3000

www.thorlabs.com

ER90B/M - September 21, 2023

Item # ER90B/M was discontinued on September 21, 2023. For informational purposes, this is a copy of the website content at that time and is valid only for the stated product.

MINI-SERIES CONSTRUCTION ACCESSORIES



Hide Overview

OVERVIEW

Features

- Rigid Construction Accessories Required for Many Complex 3D Assemblies
- · Angle Clamp Options
 - Fixed 90° Mini-Series or Ø1/2" Mounting Options
 - Continuous 360° for Mini-Series or Ø1/2" Posts
- Construction Cubes Provide Space-Saving Platform for Multiple Optical Mounts

Thorlabs' Mini-Series Angle Clamps, Brackets, and Construction Cubes provide space-saving mounting solutions. Our angle clamps give the user the ability to orient our Ø6 mm posts in multiple directions and provide rigid, stable, and compact structures that can meet many laboratory needs. The double-bored mounting holes ensure two lines of stable contact, while the aluminum thumbscrews securely fasten the posts in place. Our angle brackets provide a stable platform for constructing rigid assemblies.

For compatibility with Ø1/2" posts, Thorlabs' offers angle clamps that allow a Ø6 mm post to be mounted to a Ø1/2" post. These angle clamps are available with a fixed right-angle or continuous 360° rotation.

Thorlabs' Mini-Series Construction Cubes can be used to mount multiple optical elements close together, which alleviates the need for multiple posts and post holders. The two cube designs provide adaptable laboratory solutions to crowded table problems.

Ø6 mm to Ø6 mm Mini-Series Angle Clamps

Product Image (Click to Enlarge)			100
Item #	ER90BA (ER90B/M)	MSRA90	MSWC
Clamp Angle	90°	90°	Continuous 360°

- Rigid Construction Accessories Required for Many Complex 3D Assemblies
- Double-Bored Through Holes for Stable Two-Line Contact
- Setscrews or Thumbscrews Provide Secure Holding Force for Locking

Thorlabs' Mini Angle Clamps securely fasten our Ø6 mm mini posts at an angle to one another. The ER90BA (ER90B/M) or MSRA90 fixedangle clamp can be used to orient two posts at 90°. We also offer a variant for 360° continuous adjustment (Item # MSWC). The holes of

these clamps are double bored to provide two lines of stable contact. The ER90BA and ER90B/M each have one double-bored hole with a 5/64" (2.0 mm) or 1.3 mm (0.05") hex setscrew, respectively, and 4-40 (M3) taps on the top and bottom, allowing the clamps to be directly threaded onto a mini post. The MSRA90 and MSWC clamps each have two double-bored holes for the mini posts; thumbscrews located at either side of these clamps secure the Ø6 mm mini posts in place once the desired position is achieved. The MSWC clamp also has an additional thumbscrew to lock the angle adjustment.

Part Number	Description	Price	Availability
ER90B/M	Fixed 90° Bracket, Ø6 mm Bore and M3 Taps	\$16.31	Lead Time
MSRA90	Mini-Post Right-Angle Post Clamp, Fixed 90° Adapter	\$19.22	Today
MSWC	Mini-Post Swivel Post Clamp, 360° Continuously Adjustable	\$37.40	Today
ER90BA	Fixed 90° Bracket, Ø6 mm Bore and 4-40 Taps	\$16.31	Today

Hide Ø1/2" to Ø6 mm Angle Post Clamp

Ø1/2" to Ø6 mm Angle Post Clamp



- Mounts a Ø6 mm Mini-Series Post or Cage Rod to a Ø1/2" Post
- Right-Angle and 360° Continuous Adjustment Available
- Imperial and Metric Versions Available

Thorlabs' Ø1/2" to Ø6 mm angle post clamps are used to integrate Ø1/2" posts into miniseries constructions or cage system assemblies. These clamps are available as a fixed

right-angle, for perpendicular mounting, or with continuous 360° angle adjustment. Individual locking mechanisms for each post, as well as the rotation angle, allow for independent adjustment of each component.

The MSWCA(/M) clamp allows a Ø6 mm cage rod or mini-series post to be mounted to a Ø1/2" post with 360° continuous adjustment. The clamp features witness lines marked every 45°, as well as a 3/16" (5 mm) hex

thumbscrew to secure the swivel angle. Two additional 3/16" (5 mm) hex thumbscrews are used to secure the posts into place. The center-to-center distance between the two posts is 0.62" (15.7 mm).

The RA90TR(/M) clamp allows a Ø6 mm cage rod or mini-series post to be mounted perpendicularly to a Ø1/2" post. The design combines a highly stable clamp flexure lock for holding the Ø6 mm post that is secured using a 5/64" (2 mm) balldriver. A 3/16" (5mm) thumbscrew locking mechanism is used for attaching the clamp to the Ø1/2" post. The center-to-center distance between the two posts is 1/2" (12.7 mm).

Part Number	Description	Price	Availability
MSWCA/M	Customer Inspired! Rotating Clamp for Ø1/2" to Ø6 mm Posts, 360° Continuously Adjustable, 5 mm Hex	\$37.70	Today
RA90TR/M	Customer Inspired! Right-Angle Ø1/2" to Ø6 mm Post Clamp, 5 mm Hex Thumbscrew	\$17.82	Today
MSWCA	Customer Inspired! Rotating Clamp for Ø1/2" to Ø6 mm Posts, 360° Continuously Adjustable, 3/16" Hex	\$37.70	Today
RA90TR	Customer Inspired! Right-Angle Ø1/2" to Ø6 mm Post Clamp, 3/16" Hex Thumbscrew	\$17.82	Today
RA90TR	Customer Inspired! Right-Angle Ø1/2" to Ø6 mm Post Clamp, 3/16" Hex Thumbscrew	\$17.82	Today

Hide Mini-Series Right-Angle Plate

Mini-Series Right-Angle Plate

One-Piece Aluminum Construction for Excellent Rigidity



Click for Details A Ø6 mm Post Mounted to a Ø1/2" Post With Continuous 360° Rotation Using the MSWCA Clamp



Click to Enlarge A Ø6 mm Post Mounted Perpendicularly to a Ø1/2" Post Using the RA90TR Clamp



- Angled Rear Support Structure Reinforces Mounted Optomechanics
- Parallel and Perpendicular to Within 0.02" (0.05 mm)

Mini-Series components. This bracket provides four 4-40 (M3) clearance slots, seven 4-40 (M3) tapped holes, and

Our MSAP90(/M) Mini-Series Right-Angle Plate, based upon our popular AP90 Right-Angle Plate design, is an ideal solution for constructing rigid three-dimensional assemblies with our

4-40 (M3)
Tapped Hole (12.5 mm)

1.50"
(12.5 mm)

1.50"
(25 mm)

1.50"
(38 mm)

8 bottom

Click for Details MSAP90 Mechanical Drawing

two 4-40 (M3) counterbores oriented at 90° from an optical table surface. Its base contains two 1.0" (25.4 mm) long, 4-40 (M3) clearance slots and two 4-40 (M3) counterbores for mounting to a Mini-Series Breadboard.

	Description	Price	Availability
MSAP90/M Mini	ni-Series Right-Angle Bracket, M3 Holes	\$51.16	Today
MSAP90 Mini	ni-Series Right-Angle Bracket, 4-40 Holes	\$51.16	Today

Hide Mini-Series Construction Cubes

Mini-Series Construction Cubes

with larger optomech like Ø1/2" Posts.



Ideal for building compact structures that require a high degree of rigidity, the MSCB1 construction cube is tapped on all six surfaces, allowing our Ø6 mm mini posts to be attached to any surface (see photo to the right). The MSCB2 has three mounting surfaces, each with a #4 (M3) clearance hole that allows the assembly of three of our Ø6 mm mini posts. These cubes are machined from a solid block of aluminum on all six sides, parallel and perpendicular to within 0.002" (0.05 mm).

We also offer the MSCB3(/M) 1/2" (12.7 mm) Construction Cube with 8-32 (M4 x 0.7) mounting holes for use



Click to Enlarge Three Ø6 mm Posts Attached to an MSCB2



Six Ø6 mm Posts
Attached to an MSCB1

Part Number	Description	Price	Availability
MSCB1/M	12.7 mm Construction Cube with M3 x 0.5 Tapped Holes	\$14.55	Today
MSCB2	1/2" Construction Corner Bracket with #4 (M3) Bores	\$14.55	Today
MSCB1	1/2" Construction Cube with 4-40 Tapped Holes	\$14.55	Today