

## FINAL INSPECTION REPORT

### 2x2 75:25 PM Narrowband Coupler

Item #: PN1310R3A2  
SN: T009694

Center Wavelength: 1310 nm  
Coupling Ratio Specification  
Signal Output: 73 % - 77 %  
Tap Output: 23 % - 27 %  
Bandwidth:  $\pm 15$  nm  
Maximum Optical Power<sup>a</sup>  
With Connectors or Bare Fiber: 1 W  
Spliced: 5 W  
Fiber Type: Corning PR PM 13-U25D-H

Test Data <sup>b</sup>	
Excess Loss <sup>c</sup>	$\leq 0.5$ dB
Input-Output Path	White (Input) – White (Signal Output)
Coupling Ratio <sup>d</sup>	74.5 %
Insertion Loss <sup>e</sup>	1.45 dB
PER <sup>f</sup>	26.5 dB
Input-Output Path	White (Input) – Red (Tap Output)
Coupling Ratio <sup>d</sup>	25.5 %
Insertion Loss <sup>e</sup>	6.1 dB
PER <sup>f</sup>	21.0 dB

- a. Specifies the maximum power allowed through the component. Performance and reliability under high power conditions must be determined within the user's setup.
- b. All values are measured at room temperature without connectors through the white input port.
- c. Ratio of the input optical power to the total optical power from all output ports. It is measured at the center wavelength.
- d. Does not include losses, as this is a measurement of the output power distribution only.
- e. Includes both the split of the power between the two outputs, as well as any optical losses in the coupler.
- f. Measured with a slow axis launch at room temperature with connectors at the center wavelength through the white input port.